

▶ **PATTERN CHARACTERISTIC: Less resistance, Less friction heat, Good driving stability, Silence.**

▶ Running on paved road.

FA602

| SIZE | PLY | SPEED RANGE | RIM | | PATTERN DEPTH(mm) | LOAD INDEX | INFLATION PRESSURE (KPA) | | LOAD CAPACITY(kg) | |
|-------------|-----|-------------|--------------|---------------|-------------------|------------|--------------------------|------|-------------------|--|
| | | | STANDARD RIM | ALLOWABLE RIM | | | SINGLE | DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 10.9 | 144/142 | 720 | 2800 | 2650 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25 | 10.9 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |

▶ **PATTERN CHARACTERISTIC: High driving power, Excellent load performance, Anti-skid, Less friction heat.**

▶ Running on paved road.

FA606

| SIZE | PLY | SPEED RANGE | RIM | | PATTERN DEPTH(mm) | LOAD INDEX | INFLATION PRESSURE (KPA) | | LOAD CAPACITY(kg) | |
|-------------|-----|-------------|--------------|---------------|-------------------|------------|--------------------------|------|-------------------|--|
| | | | STANDARD RIM | ALLOWABLE RIM | | | SINGLE | DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 15 | 144/142 | 720 | 2800 | 2650 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25 | 15 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |
| 12R22.5 | 16 | M | 9.00 | 8.25 | 16 | 150/147 | 830 | 3350 | 3075 | |
| | 18 | M | | | | 152/149 | 930 | 3550 | 3250 | |
| 295/80R22.5 | 16 | M | 9.00 | 8.25 | 15 | 150/147 | 830 | 3350 | 3075 | |
| | 18 | M | | | | 152/149 | 900 | 3550 | 3250 | |
| 255/70R22.5 | 14 | M | 7.50 | 7.50V 8.00 | 13 | 138/134 | 760 | 2360 | 2120 | |
| | 16 | M | | | | 140/137 | 830 | 2500 | 2300 | |
| 315/80R22.5 | 18 | M | 9.00 | 9.75 | 15 | 154/151 | 830 | 3750 | 3450 | |
| | 20 | M | | | | 156/153 | 900 | 4000 | 3650 | |
| 11R24.5 | 14 | M | 8.25 | 7.50 | 15 | 146/143 | 720 | 3000 | 2725 | |
| | 16 | M | | | | 148/146 | 830 | 3250 | 3000 | |
| 285/75R24.5 | 14 | M | 8.25 | - | 15 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 147/144 | 830 | 3075 | 2800 | |

▶ **PATTERN CHARACTERISTIC: High speed, Wear-resistance, Less friction heat, More comfortable, Low noise.**

▶ Running on paved road.

FA616

| SIZE | PLY | SPEED RANGE | RIM | | PATTERN DEPTH(mm) | LOAD INDEX | INFLATION PRESSURE (KPA) | | LOAD CAPACITY(kg) | |
|-------------|-----|-------------|--------------|---------------|-------------------|------------|--------------------------|------|-------------------|--|
| | | | STANDARD RIM | ALLOWABLE RIM | | | SINGLE | DUAL | | |
| 315/80R22.5 | 18 | M | 9.00 | 9.75 | 15 | 154/151 | 830 | 3750 | 3450 | |
| | 20 | M | | | | 156/153 | 900 | 4000 | 3650 | |

▶ **PATTERN CHARACTERISTIC: High driving power, Excellent load, Good braking, Better endurance.**

▶ Running on paved road.

FA608

| SIZE | PLY | SPEED RANGE | RIM | | PATTERN DEPTH(mm) | LOAD INDEX | INFLATION PRESSURE (KPA) | | LOAD CAPACITY(kg) | |
|-------------|-----|-------------|--------------|---------------|-------------------|------------|--------------------------|------|-------------------|--|
| | | | STANDARD RIM | ALLOWABLE RIM | | | SINGLE | DUAL | | |
| 11R22.5 | 14 | L | 8.25 | 7.50 | 21.3 | 144/142 | 720 | 2800 | 2650 | |
| | 16 | L | | | | 146/143 | 830 | 3000 | 2725 | |
| 295/75R22.5 | 14 | K | 9.00 | 8.25 | 21.3 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | K | | | | 146/143 | 830 | 3000 | 2725 | |
| 11R24.5 | 14 | L | 8.25 | 7.50 | 21 | 146/143 | 720 | 3000 | 2725 | |
| | 16 | L | | | | 149/146 | 830 | 3250 | 3000 | |
| 285/75R24.5 | 14 | L | 8.25 | - | 21 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | L | | | | 147/144 | 830 | 3075 | 2800 | |

▶ **PATTERN CHARACTERISTIC: High driving power, Less friction heat, Anti-skid, Better endurance.**

▶ Running on paved road.

FA606+

| SIZE | PLY | SPEED RANGE | RIM | | PATTERN DEPTH(mm) | LOAD INDEX | INFLATION PRESSURE (KPA) | | LOAD CAPACITY(kg) | |
|-------------|-----|-------------|--------------|---------------|-------------------|------------|--------------------------|------|-------------------|--|
| | | | STANDARD RIM | ALLOWABLE RIM | | | SINGLE | DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 15 | 144/142 | 720 | 2800 | 2650 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25 | 15 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |
| 11R24.5 | 14 | M | 8.25 | 7.50 | 15 | 146/143 | 720 | 3000 | 2725 | |
| | 16 | M | | | | 149/146 | 830 | 3250 | 3000 | |
| 285/75R24.5 | 14 | M | 8.25 | - | 15 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 147/144 | 830 | 3075 | 2800 | |

▶ **PATTERN CHARACTERISTIC: High driving power, Anti-skid, Wear-resistance.**

▶ Running on paved or unpaved road.

FA618

| SIZE | PLY | SPEED RANGE | RIM | | PATTERN DEPTH(mm) | LOAD INDEX | INFLATION PRESSURE (KPA) | | LOAD CAPACITY(kg) | |
|-------------|-----|-------------|--------------|---------------|-------------------|------------|--------------------------|------|-------------------|--|
| | | | STANDARD RIM | ALLOWABLE RIM | | | SINGLE | DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 22.5 | 144/142 | 720 | 2800 | 2650 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |
| 11R24.5 | 14 | M | 8.25 | 7.50 | 22.5 | 146/143 | 720 | 3000 | 2725 | |
| | 16 | M | | | | 149/146 | 830 | 3250 | 3000 | |
| 285/75R24.5 | 14 | M | 8.25 | - | 22.5 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 147/144 | 830 | 3075 | 2800 | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25 | 22.5 | 144/141 | 760 | 2800 | 2575 | |
| | 16 | M | | | | 146/143 | 830 | 3000 | 2725 | |