


PC

Passenger Car / Turismo / Pneu de Turismo / Tourisme / السيارات الصغيرة

MARSHAL

Max. Performance

MARSHAL MU12



English

- Safe handling & Braking Performance
- 4 wide grooves improve water evacuation on wet road



Español

- Manejo seguro y rendimiento al frenar
- 4 Surcos amplios que mejoran la expulsión del agua en caminos húmedos



Português

- Condução segura e alto desempenho em frenagens.
- 4 sulcos largos melhoram a drenagem da água em pistas molhadas



Français

- Manœuvrabilité et freinage en toute sécurité
- 4 rainures larges permettant une excellente évacuation de l'eau sur sol mouillé



عربي

- الأداء الامن والتمثل للماكين.
- 4 أخاديد واسعة لتحسين إخلاء المياه على الطرق المبتلة.



MU12

Table with 15 columns: Rim, Tire Size, Measuring Rim Width, Approved Rim Width, Max. Air Pressure, Max. Load, Section Width, Overall Diameter, Tread Depth, Static Loaded Radius, Rolling Circumference, UTQG, Rim Protector. Rows are categorized by rim size (20", 19", 18", 17") and list various tire models with their specifications.

XL : Extra Load



PC

Passenger Car / Turismo / Pneu de Turismo / Tourisme / السيارات الصغيرة

MARSHAL

Max. Performance

MARSHAL MU12



English

- Safe handling & Braking Performance
- 4 wide grooves improve water evacuation on wet road



Español

- Manejo seguro y rendimiento al frenar
- 4 Surcos amplios que mejoran la expulsión del agua en caminos húmedos



Português

- Condução segura e alto desempenho em frenagens.
- 4 sulcos largos melhoram a drenagem da água em pistas molhadas



Français

- Manœuvrabilité et freinage en toute sécurité
- 4 rainures larges permettant une excellente évacuation de l'eau sur sol mouillé



عربي

- الأداء الآمن والامتثال للمناخ
- 4 أخاديد واسعة لتحسين إخلاء المياه على الطرق المبللة



MU12

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width	Overall Diameter	Tread Depth	Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector					
				bar	psi	kg	lbs								mm	inch	mm	inch	
Black Sidewall																			
17"	205/40 ZR17 XL 84W	7.5	7.0 - 8.0	3.4	50	500	1102	212	8.3	596	23.5	7.6	9.6	280	1818	320	AA	A	o
	205/45 ZR17 XL 88Y	7.0	6.5 - 7.5	3.4	50	560	1235	206	8.1	616	24.3	7.6	9.6	288	1879	320	AA	A	o
	205/45 ZR17 XL 88W	7.0	6.5 - 7.5	3.4	50	560	1235	206	8.1	616	24.3	7.6	9.6	288	1879	320	AA	A	o
16"	205/50 ZR17 XL 93W	6.5	5.5 - 7.5	3.4	50	650	1433	214	8.4	638	25.1	8.1	10.2	296	1946	320	AA	A	o
	225/55 ZR16 95W	7.0	6.0 - 8.0	3.5	51	690	1521	233	9.2	654	25.7	7.8	9.8	300	1995	320	AA	A	o
	215/55 ZR16 97W	7.0	6.0 - 7.5	3.4	50	730	1609	226	8.9	642	25.3	7.8	9.8	295	1958	320	AA	A	o
	215/55 R16 93W	7.0	6.0 - 7.5	3.5	51	650	1433	226	8.9	642	25.3	7.8	9.8	295	1958	320	AA	A	o
	205/45 ZR16 XL 87W	7.0	6.5 - 7.5	3.4	50	545	1201	206	8.1	590	23.2	7.8	9.8	275	1800	320	AA	A	o
	205/45 R16 XL 87V	7.0	6.5 - 7.5	3.4	50	545	1201	206	8.1	590	23.2	7.8	9.8	275	1800	320	AA	A	o
	205/50 ZR16 87W	6.5	5.5 - 7.5	3.5	51	545	1201	214	8.4	612	24.1	7.8	9.8	283	1867	320	AA	A	o
	205/55 ZR16 91W	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	7.8	9.8	291	1928	320	AA	A	o
	205/55 R16 XL 94V	6.5	5.5 - 7.5	3.4	50	670	1477	214	8.4	632	24.9	7.8	9.8	291	1928	320	AA	A	o
	205/55 R16 91V	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	7.8	9.8	291	1928	320	AA	A	o
	195/45 R16 XL 84V	6.5	6.0 - 7.5	3.4	50	500	1102	195	7.7	582	22.9	8.1	10.2	272	1775	320	AA	A	o
	195/50 R16 XL 88V	6.0	5.5 - 7.0	3.4	50	560	1235	201	7.9	602	23.7	7.8	9.8	280	1836	320	AA	A	o
195/55 R16 87V	6.0	5.5 - 7.0	3.5	51	545	1201	201	7.9	620	24.4	7.8	9.8	287	1891	320	AA	A	o	
195/55 R16 87H	6.0	5.5 - 7.0	3.5	51	545	1201	201	7.9	620	24.4	7.8	9.8	287	1891	320	AA	A	o	
185/50 R16 81V	6.0	5.0 - 6.5	3.5	51	462	1019	194	7.6	592	23.3	7.8	9.8	276	1806	320	AA	A	o	
15"	195/50 R15 XL 86V	6.0	5.5 - 7.0	3.4	50	530	1168	201	7.9	577	22.7	7.8	9.8	267	1760	320	AA	A	o
	195/50 R15 XL 86H	6.0	5.5 - 7.0	3.4	50	530	1168	201	7.9	577	22.7	7.8	9.8	267	1760	320	AA	A	o
	195/55 R15 85V	6.0	5.5 - 7.0	3.5	51	515	1135	201	7.9	595	23.4	7.8	9.8	274	1815	320	AA	A	o
	195/55 R15 85H	6.0	5.5 - 7.0	3.5	51	515	1135	201	7.9	595	23.4	7.8	9.8	274	1815	320	AA	A	o
	185/55 R15 82V	6.0	5.0 - 6.5	3.5	51	475	1047	194	7.6	585	23.0	7.8	9.8	270	1784	320	AA	A	o
	185/55 R15 82H	6.0	5.0 - 6.5	3.5	51	475	1047	194	7.6	585	23.0	7.8	9.8	270	1784	320	AA	A	o

XL : Extra Load

XRP Run-flat

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width	Overall Diameter	Tread Depth	Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector					
				bar	psi	kg	lbs								mm	inch	mm	inch	
Black Sidewall																			
18"	225/40 ZR18 88Y	8.0	7.5 - 9.0	3.5	51	560	1235	230	9.1	637	25.1	7.5	9.4	299	1943	320	AA	A	o
17"	205/45 R17 84V	7.0	6.5 - 7.5	3.5	51	500	1102	206	8.1	616	24.3	7.5	9.4	288	1879	320	A	A	o