



WRANGLER® ALL-TERRAIN ADVENTURE WITH KEVLAR®

OUR MOST VERSATILE ALL-TERRAIN TIRE WITH THE TOUGHNESS OF DUPONT™ KEVLAR® TO GO OFF-ROAD AT A MOMENT'S NOTICE

The new Wrangler® All-Terrain Adventure features a layer made with Kevlar® – a material that offers superb toughness. Whether your customers like to explore rocky trails or never leave the pavement, you can confidently recommend this tire to them over the competition!

- **RUGGED STRENGTH** provided by a layer of DuPont™ Kevlar®
- **HELPS PREVENT CUTS IN THE SIDEWALL** with its Durawall™ Technology
- **VERSATILE OFF-ROAD TRACTION IN WET, MUDDY CONDITIONS** as a result of its open tread pattern
- **SUPERB TRACTION IN THE SNOW AND RAIN** thanks to a special tread compound and biting edges that help grip the road
- **20% LONGER TREAD LIFE LIMITED WARRANTY†** (60,000 Mile/95,000 Kilometre Tread Life Limited Warranty*)
- **PRO-GRADE PACKAGE FOR HEAVY-DUTY TRUCKS ON LT SIZES INCLUDES:**
Two layers of Kevlar® and 30% more steel‡ for enhanced toughness and the Severe Snow Conditions Symbol** for winter weather driving

60000
MILE TREAD LIFE
LIMITED WARRANTY*

95,000 Kilometre Tread
Life Limited Warranty



Severe Snow
Conditions Symbol**

†Compared to other Wrangler tires.

*See warranty brochure for complete details.

‡Compared to standard load tires.

**LT sizes only

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



GOODYEAR
MORE DRIVEN.

WRANGLER® ALL-TERRAIN ADVENTURE WITH KEVLAR®

OE FITMENTS FOR FUTURE SALES

To keep consumers coming back for more, the new Wrangler® All-Terrain Adventure will be our OE, on- and off-road fitment. It will be featured on exciting future trucks and full-size SUVs!

WRANGLER ALL-TERRAIN ADVENTURE AVAILABLE SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32NDS)	REVS/MILE	UTOG
31X10.50R15LT	109R	C	OWL	748510571	219161	7.0 - 9.0	8.5	10.6	30.8	2,270	15	681	
235/70R16	106T	SL	BSL	758043571	219132	6.0 - 8.0	7.0	9.5	29.0	2,095	12	721	640 A B
235/70R16	106T	SL	BSL	758079572	220309	6.0 - 8.0	7.0	9.5	29.0	2,095	12	721	640 A B
245/70R16	107T	SL	OWL	758762571	219140	6.5 - 8.0	7.0	9.8	29.5	2,150	12	708	640 A B
245/75R16	111T	SL	OWL	758059571	219136	6.5 - 8.0	7.0	9.8	30.5	2,405	12	686	640 A B
255/70R16	111T	SL	OWL	758062571	219138	6.5 - 8.5	7.5	10.2	30.1	2,405	12	695	640 A B
265/70R16	112T	SL	OWL	758045571	219134	7.0 - 9.0	8.0	10.7	30.6	2,470	12	682	640 A B
265/75R16	116T	SL	OWL	758057571	219135	7.0 - 9.0	7.5	10.5	31.7	2,755	12	660	640 A B
235/70R17	111T	XL	OWL	758078571	219152	6.0 - 8.0	7.0	9.5	30.0	2,405	12	697	640 A B
235/75R17	109T	SL	BSL	758089572	220536	6.0 - 8.0	6.5	9.3	30.9	2,270	12	677	640 A B
245/65R17	107T	SL	BSL	758592572	219133	7.0 - 8.5	7.0	9.8	29.5	2,150	12	708	640 A B
245/65R17	107T	SL	BSL	758592571	220310	7.0 - 8.5	7.0	9.8	29.5	2,150	12	708	640 A B
245/70R17	110T	SL	BSL	758060572	219137	6.5 - 8.0	7.0	9.8	30.6	2,335	12	684	640 A B
245/70R17	110T	SL	OWL	758080571	220321	6.5 - 8.0	7.0	9.8	30.6	2,335	12	684	640 A B
255/65R17	110T	SL	OWL	758069571	219146	7.0 - 9.0	7.5	10.2	30.1	2,335	12	691	640 A B
255/70R17	112T	SL	OWL	758067571	219144	6.5 - 8.5	7.5	10.3	31.1	2,470	12	672	640 A B
265/65R17	112T	SL	OWL	758061571	219139	7.5 - 9.5	8.0	10.7	30.6	2,470	12	684	640 A B
265/70R17	115T	SL	OWL	758042571	219131	7.0 - 9.0	8.0	10.7	31.7	2,680	12	660	640 A B
265/70R17	115T	SL	BSL	758042572	220308	7.0 - 9.0	8.0	10.7	31.7	2,680	12	660	640 A B
255/65R18	111T	SL	BSL	758088572	220341	7.0 - 9.0	7.5	10.2	31.1	2,405	12	672	640 A B
255/70R18	113T	SL	BSL	758074572	219149	6.5 - 8.5	7.5	10.2	32.1	2,535	12	651	640 A B
265/60R18	110T	SL	OWL	758076571	219150	7.5 - 9.5	8.0	10.7	30.5	2,335	12	685	640 A B
265/65R18	114T	SL	OWL	758068571	219145	7.5 - 9.5	8.0	10.7	31.5	2,600	12	663	640 A B
265/70R18	116T	SL	OWL	758070571	219147	7.0 - 9.0	8.0	10.7	32.6	2,755	12	640	640 A B
275/65R18	116T	SL	OWL	758066571	219143	7.5 - 9.5	8.0	11.0	32.1	2,755	12	651	640 A B
275/65R18	116T	SL	BSL	758081572	220322	7.5 - 9.5	8.0	11.0	32.1	2,755	12	651	640 A B
255/60R19	109T	SL	BSL	758083572	220340	7.0 - 9.0	7.5	10.2	31.1	2,270	12	672	640 A B
275/55R20	113T	SL	BSL	758065572	219141	7.5 - 9.5	8.5	11.2	31.9	2,535	12	655	640 A B
275/60R20	115T	SL	OWL	758073571	219148	7.5 - 9.5	8.0	11.0	33.0	2,680	12	634	640 A B
275/60R20	115T	SL	BSL	758082572	220323	7.5 - 9.5	8.0	11.0	33.0	2,680	12	634	640 A B

WRANGLER ALL-TERRAIN ADVENTURE PRO-GRADE AVAILABLE SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32NDS)	REVS/MILE	UTOG
LT215/85R16	115R	E	BSL	748517572	219162	5.5 - 7.0	6.0	8.6	30.5	2,680	15	688	
LT225/75R16	115R	E	BSL	748748572	219159	6.0 - 7.0	6.0	8.8	29.3	2,680	15	714	
LT235/85R16	120R	E	BSL	748745572	219158	6.0 - 7.5	6.5	9.3	31.7	3,042	15	659	
LT245/75R16	120S	E	BSL	748103572	225437	6.5 - 8.0	7.0	9.8	30.5	3,042	15	686	
LT245/75R16	120S	E	OWL	748103571	225438	6.5 - 8.0	7.0	9.8	30.5	3,042	15	686	
LT265/75R16	123R	E	BSL	748746572	219157	7.0 - 8.0	7.5	10.5	31.7	3,415	15	660	
LT265/75R16	123R	E	OWL	748746571	220325	7.0 - 8.0	7.5	10.5	31.7	3,415	15	660	
LT285/75R16	126R	E	OWL	748585571	219166	7.5 - 9.0	8.0	11.3	32.8	3,750	15	637	
LT285/75R16	126R	E	BSL	748585572	220328	7.5 - 9.0	8.0	11.3	32.8	3,750	15	637	
LT235/80R17	120R	E	BSL	748635572	219165	6.0 - 7.5	6.5	9.3	31.8	3,085	15	654	
LT245/70R17	119R	E	OWL	748469571	219169	6.5 - 8.0	7.0	9.8	30.6	3,000	15	684	
LT245/70R17	119R	E	BSL	748469572	220329	6.5 - 8.0	7.0	9.8	30.6	3,000	15	684	
LT245/75R17	121S	E	OWL	748104571	225439	6.5 - 7.5	7.0	9.8	31.5	3,195	15	663	
LT245/75R17	121S	E	BSL	748104572	225440	6.5 - 7.5	7.0	9.8	31.5	3,195	15	663	
LT265/70R17	121S	E	OWL	748661571	225841	7.0 - 8.5	8.0	10.7	31.7	3,195	15	660	
LT265/70R17	121S	E	BSL	748661572	225843	7.0 - 8.5	8.0	10.7	31.7	3,195	15	660	
LT285/70R17	121R	E	OWL	748096571	219170	7.5 - 9.0	8.5	11.5	32.8	3,195	15	638	
LT285/70R17	121R	E	BSL	748096572	220330	7.5 - 9.0	8.5	11.5	32.8	3,195	15	638	
LT265/70R18	124S	E	BSL	748014572	225842	7.0 - 9.0	8.0	10.7	32.6	3,527	15	638	
LT275/65R18	123S	E	OWL	748965571	225844	7.5 - 9.0	8.0	11.0	32.1	3,415	15	651	
LT275/70R18	125S	E	BSL	748108572	225461	7.0 - 8.5	8.0	11.0	33.2	3,640	15	630	
LT275/70R18	125S	E	OWL	748108571	225462	7.0 - 8.5	8.0	11.0	33.2	3,640	15	630	
LT285/65R18	125R	E	BSL	748093572	220338	8.0 - 10.0	8.5	11.5	32.6	3,640	15	639	
LT265/60R20	121R	E	BSL	748097572	220332	7.5 - 9.5	8.0	10.7	32.5	3,197	15	640	
LT275/65R20	126S	E	OWL	748303571	226061	7.5 - 9.5	8.0	11.0	34.1	3,750	15	610	
LT275/65R20	126S	E	BSL	748303572	226062	7.5 - 9.5	8.0	11.0	34.1	3,750	15	610	
LT285/55R20	122R	E	BSL	748101572	220336	8.0 - 10.0	9.0	11.7	32.4	3,305	15	646	
LT285/60R20	125R	E	BSL	748015572	220337	8.0 - 10.0	8.5	11.5	33.5	3,638	15	622	
LT305/55R20	121R	E	BSL	748094572	219173	8.5 - 11.0	9.5	12.4	33.2	3,195	15	622	

POPULAR WRANGLER ALL-TERRAIN ADVENTURE COMPETITIVE REPLACEMENTS:

- Michelin LTX A/T 2
- BFGoodrich All-Terrain T/A KO
- Bridgestone Dueler A/T Rev0 2

PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death.

